

ADAMS

Advanced **D**ata mining **A**nd **M**achine learning **S**ystem

Module: adams-meka-webservice

WS

MEKA

Peter Reutemann

December 20, 2018

©2017



THE UNIVERSITY OF
WAIKATO
Te Whare Wānanga o Waikato



Except where otherwise noted, this work is licensed under
<http://creativecommons.org/licenses/by-sa/4.0/>

Contents

| | | |
|----------|-----------------------|-----------|
| 1 | Set up | 7 |
| 1.1 | Client | 7 |
| 1.2 | Server | 9 |
| 2 | Usage | 11 |
| 2.1 | Classifiers | 11 |
| 2.2 | Filters | 11 |
| 3 | Development | 13 |
| | Bibliography | 15 |

List of Figures

| | | |
|-----|---|----|
| 1.1 | Tag in the WSDL to change for the clients. | 8 |
| 1.2 | Displaying dialog with URL the webservice binds to. | 9 |
| 2.1 | Callable actor for transforming datasets. | 12 |

Chapter 1

Set up

The default set up for the webservice is to run on the local machine, or *localhost*. If you want to publish the webservice, either within a LAN or over the internet, then you need to update the URL and/or port that the webservice binds to and is available for clients.

1.1 Client

If you use ADAMS clients, you need to change the WSDL for the MEKA webservice to point the clients to the right address. You can find the WSDL for the webservice at the following location:

```
resources/wsd1/meka/MekaService.wsdl
```

In this file, change the *location* attribute of the *soap:address* tag appropriately. For instance, from this:

```
<soap:address location="http://localhost:9090/MekaServicePort"/>
```

to this:

```
<soap:address location="http://meka.blah.com:8080/MekaServicePort"/>
```




Figure 1.1: Tag in the WSDL to change for the clients.

1.2 Server

In addition to the changes to the WSDL as described in the section on the *Client*, the server requires another modification when launched from the flow. In case of the example server workflow¹, you can do this by changing the *URL* property located here:

- *WSServer* actor
- *webService* property
- *URL* property

For instance, if the server's running the webservice is *mekah.blah.com* and is supposed to use port 8080, then use the URL *http://mekah.blah.com:8080/MekaServicePort*.

NB: Ensure that the port is not blocked by a firewall running on the server or already used otherwise.




Figure 1.2: Displaying dialog with URL the webservice binds to.

¹ adams-meka-webservice-meka-webservice.flow

Chapter 2

Usage

Before you can use the webservice, you need to start the server side. You can do this by simply starting the example server flow¹.

2.1 Classifiers

The webservice offers the following functionality for classifiers:

- *cross-validation* – cross-validates a specified classifier setup on a provided dataset and returns the statistics.²
- *train* – trains a classifier setup on a provided dataset and places the model into a lookup table in internal storage for future use.³
- *test* – evaluates a model from the lookup table in internal storage with a new dataset and returns the statistics.⁴
- *predict* – uses a model to generate predictions for a provided dataset.⁵
- *list* – lists all the names of the currently stored classifier models.⁶
- *display* – returns the string representation of a stored classifier model.⁷
- *download* – downloads a previously trained a classifier model.⁸

2.2 Filters

The webservice also allows you to transform datasets using MEKA filters. This works by providing a dataset and the name of the callable actor on the server. You can define an arbitrary number of callable actors that transform datasets. The only requirement is that they accept a *weka.core.Instances* object and generate such one as well.⁹

¹adams-meka-webservice-meka-webservice.flow

²adams-meka-webservice-crossvalidate-classifier.flow

³adams-meka-webservice-train-classifier.flow

⁴adams-meka-webservice-test-classifier.flow

⁵adams-meka-webservice-predict-classifier.flow

⁶adams-meka-webservice-list-classifiers.flow

⁷adams-meka-webservice-display-classifier.flow

⁸adams-meka-webservice-download-classifier.flow

⁹adams-meka-webservice-transform.flow




Figure 2.1: Callable actor for transforming datasets.

Chapter 3

Development

The default webservice implementation, `adams.flow.webservice.SimpleMekaService`, is a very simply version providing the functionality. All processing happens in a single thread. If you require a version that scales better and can handle more and concurrent requests, then you might want to implement your own backend. This is quite simple, as you only need to create a class that implements the following interfaces:

- `nz.ac.waikato.adams.webservice.meka.MekaService`
- `adams.flow.webservice.OwnedByMekaServiceWS`

Or, you can simply subclass `adams.flow.webservice.SimpleMekaService` and override the method that needs your attention.

The class needs to be placed in the following package:

```
adams.flow.webservice.meka
```


Bibliography

- [1] *ADAMS* – Advanced Data mining and Machine learning System
<https://adams.cms.waikato.ac.nz/>
- [2] *WSDL* – Web Services Description Language
http://en.wikipedia.org/wiki/Web_Services_Description_Language
- [3] *SOAP* – Simple Object Access Protocol
<http://en.wikipedia.org/wiki/SOAP>