

ADAMS

Advanced **D**ata mining **A**nd **M**achine learning **S**ystem

Module: adams-weka-webservice

WS



Peter Reutemann
Michael Fowke

December 24, 2014

©2012-2014



THE UNIVERSITY OF
WAIKATO
Te Whare Wānanga o Waikato



Except where otherwise noted, this work is licensed under
<http://creativecommons.org/licenses/by-sa/3.0/>

Contents

1	Set up	7
1.1	Client	7
1.2	Server	9
2	Usage	11
2.1	Classifiers	11
2.2	Clusterers	12
2.3	Filters	12
3	Development	15
	Bibliography	17

List of Figures

1.1	Tag in the WSDL to change for the clients.	8
1.2	Displaying dialog with URL the webservice binds to.	9
2.1	Callable actor for transforming datasets.	13

Chapter 1

Set up

The default set up for the webservice is to run on the local machine, or *localhost*. If you want to publish the webservice, either within a LAN or over the internet, then you need to update the URL and/or port that the webservice binds to and is available for clients.

1.1 Client

If you use ADAMS clients, you need to change the WSDL for the WEKA webservice to point the clients to the right address. You can find the WSDL for the webservice at the following location:


```
resources/wsd1/weka/WekaService.wsdl
```

In this file, change the *location* attribute of the *soap:address* tag appropriately. For instance, from this:

```
<soap:address location="http://localhost:9090/WekaServicePort"/>
```

to this:

```
<soap:address location="http://weka.blah.com:8080/WekaServicePort"/>
```



```
WekaService.wsdl (/research/fracpete/development/projects/a...ka-webservice/src/main/resource)
File Edit View Search Tools Documents Help
New Open Save Print... Undo Redo Cut Copy Paste Find Replace
WekaService.wsdl
671 </wsdl:operation>
672
673 <wsdl:operation name = "listClusterers">
674 <soap:operation soapAction="" style = "document"/>
675 <wsdl:input name = "listClusterers">
676 <soap:body use = "literal"/>
677 </wsdl:input>
678 <wsdl:output name = "listClusterersResponse">
679 <soap:body use = "literal"/>
680 </wsdl:output>
681 </wsdl:operation>
682
683 </wsdl:binding>
684
685
686 <wsdl:service name="WekaServiceService">
687 <wsdl:port name="WekaServicePort" binding="tns:WekaServiceServiceSoapBinding">
688 <!-- embedded deployment -->
689 <soap:address location="http://localhost:9090/WekaServicePort"/>
690 <!-- standalone Tomcat deployment -->
691 <!-- soap:address location="http://localhost:8080/wsdl_first-<cxfl-version>/services/adv1
692 </wsdl:port>
693 </wsdl:service>
694 </wsdl:definitions>
695
Ln 689, Col 7 INS
```

Figure 1.1: Tag in the WSDL to change for the clients.

1.2 Server

In addition to the changes to the WSDL as described in the section on the *Client*, the server requires another modification when launched from the flow. In case of the example server workflow¹, you can do this by changing the *URL* property located here:

- *WSServer* actor
- *webService* property
- *URL* property

For instance, if the server's running the webservice is *weka.blah.com* and is supposed to use port 8080, then use the URL *http://weka.blah.com:8080/WekaServicePort*.

NB: Ensure that the port is not blocked by a firewall running on the server or already used otherwise.




Figure 1.2: Displaying dialog with URL the webservice binds to.

¹adams-weka-webservice-weka-webservice.flow

Chapter 2

Usage

Before you can use the webservice, you need to start the server side. You can do this by simply starting the example server flow¹.

2.1 Classifiers

The webservice offers the following functionality for classifiers:

- *cross-validation* – cross-validates a specified classifier setup on a provided dataset and returns the statistics.²
- *train* – trains a classifier setup on a provided dataset and caches the model for future use.³
- *test* – evaluates a cached model with a new dataset and returns the statistics.⁴
- *predict* – uses a cached model to generate predictions for a provided dataset.⁵
- *list* – lists all the names of the currently cached classifier models.⁶
- *display* – returns the string representation of a cached classifier model.⁷
- *download* – downloads a previously trained a classifier model.⁸
- *optimize* – performs parameter-optimization for a classifier using a dataset, for an arbitrary number of search parameter settings using the `weka.classifiers.meta.MultiSearch` meta-classifier. The best setup is then returned.⁹

NB: If the number of cached classifier models is too small, then simply change that setting on the server (`WSServer` → `webService` → `classifierCacheSize`).

¹adams-weka-webservice-weka-webservice.flow

²adams-weka-webservice-crossvalidate-classifier.flow

³adams-weka-webservice-train-classifier.flow

⁴adams-weka-webservice-test-classifier.flow

⁵adams-weka-webservice-predict-classifier.flow

⁶adams-weka-webservice-list-classifiers.flow

⁷adams-weka-webservice-display-classifier.flow

⁸adams-weka-webservice-download-classifier.flow

⁹adams-weka-webservice-optimize-classifier-multi-search.flow

2.2 Clusterers

The webservice offers the following functionality for clusterers:

- *train* – trains a clusterer setup on a provided dataset and caches the model for future use.¹⁰
- *predict* – uses a cached model to predict cluster membership for a provided dataset.¹¹
- *list* – lists all the names of the currently cached clusterer models.¹²
- *display* – returns the string representation of a cached clusterer model.¹³
- *download* – downloads a previously trained a clusterer model.¹⁴

NB: If the number of cached classifier models is too small, then simply change that setting on the server (*WSServer* → *webService* → *clustererCacheSize*).

2.3 Filters

The webservice also allows you to transform datasets using WEKA filters. This works by providing a dataset and the name of the callable actor on the server. You can define an arbitrary number of callable actors that transform datasets. The only requirement is that they accept a *weka.core.Instances* object and generate such one as well.¹⁵

¹⁰adams-weka-webservice-train-clusterer.flow

¹¹adams-weka-webservice-predict-clusterer.flow

¹²adams-weka-webservice-list-clusterers.flow

¹³adams-weka-webservice-display-clusterer.flow

¹⁴adams-weka-webservice-download-clusterer.flow

¹⁵adams-weka-webservice-transform.flow




Figure 2.1: Callable actor for transforming datasets.

Chapter 3

Development

The default webservice implementation, `adams.flow.webservice.SimpleWekaService`, is a very simply version providing the functionality. All processing happens in a single thread. If you require a version that scales better and can handle more and concurrent requests, then you might want to implement your own backend. This is quite simple, as you only need to create a class that implements the following interfaces:

- `nz.ac.waikato.adams.webservice.weka.WekaService`
- `adams.flow.webservice.OwnedByWekaServiceWS`

Or, you can simply subclass `adams.flow.webservice.SimpleWekaService` and override the method that needs your attention.

The class needs to be placed in the following package:

```
adams.flow.webservice
```


Bibliography

- [1] *ADAMS* – Advanced Data mining and Machine learning System
<https://adams.cms.waikato.ac.nz/>
- [2] *WSDL* – Web Services Description Language
http://en.wikipedia.org/wiki/Web_Services_Description_Language
- [3] *SOAP* – Simple Object Access Protocol
<http://en.wikipedia.org/wiki/SOAP>